TXS-865HT

Order no.: 0255310

PRODUCT INFORMATION

The improvement of the transmission quality and maximising the operating range ensure reliability and provide flexibility!
These features have been realised by an innovative circuit design and a switchable transmitting power. A high-quality wireless audio transmission of up to 300 m in a free field outdoors is thus possible without any problems!

Rapid transmission: due to REMOSET, the frequency of a corresponding hand-held transmitter or pocket transmitter can easily be set up via the receiver. It is possible to remotely set the desired transmission channel at the transmitter via radio signal, no visual contact required. This can even be done during a live performance! An intelligent carrier analysis method provides user support by only allowing transmission channels on which no other transmitter is active.

Dynamic hand-held UHF PLL transmitter,
with REMOSET technology.

- Dynamic microphone cartridge, cardioid polar pattern
- 124 selectable channels in 6 channel groups (506-542 MHz)
- Adjustable sensitivity (12 dB to -18 dB)
- Lock function/mute function
- Backlit LCD for indicating channel and battery status
- Switchable transmitting power: 10 mW/50 mW (EIRP)
- Power supply via 2 x 1.5 V battery AA size (not supplied)
- Supplied with robust transport case and stand clamp

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

TASTENWELT, 05/2018
“300 metres operating range was a feature which was quite challenging during the test [...] and the TXS-865HT is definitely able to reach such an extraordinary operating range.”

How many wireless systems TXS-865... can be operated simultaneously?
With optimum local conditions, it is possible to operate up to 10 wireless systems TXS-865... with 2 microphones each simultaneously.

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

TXS-865HT	
Description	hand-held microphone transmitter
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10 mW/50 mW,switchable
Power supply	2 x batt. AA size,alkaline
Operating time	> 25 h
Audio frequency range	50-16,000 Hz
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 50 mm x 250 mm
Weight	350 g
Packaging dimensions (W x H x L)	0.17 x 0.08 x 0.37 m
Gross weight	1.143 kg
Net weight	0.854 kg

TXS-865HT

EAN code	4007754239171
Net weight	0.854 kg