ULM-164/SW

Order no.: 0202240

PRODUCT INFORMATION

Universal line mixer,
6 channels.

- 6 stereo inputs/mono inputs
- 2 stereo outputs, independent of each other (master 1 via RCA and 6.3 mm jack), 1 mono output
- 3-way equalizer
- LED VU meter, switchable for both outputs
- Clip LED for each channel
- Balance controls with centre click for the stereo input channels
- Extended muting function
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RU

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

ULM-164/SW	
No. of channels	6
No. of inputs	12
Line input	150 mV/50 kΩ (stereo), 6 x RCA L/R 150 mV/25 kΩ (mono), 6 x 6.3 mm jack, unbal.
Master output	1 V/600 Ω (stereo), 2 x RCA (1 x 6.3 mm) L/R 2 V/600 Ω (mono), 1 x 6.3 mm jack
Headphones	≥ 8 Ω, 1 x 6.3 mm jack
Frequency range	20-20,000 Hz
THD	0.05%
S/N ratio	69 dB, unweighted
Equalizer bass	±12 dB/80 Hz
Equalizer midrange	±12 dB/1 kHz
Equalizer treble	±12 dB/10 kHz
Power supply	˜ 230 V/50 Hz/10 VA
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	10 VA
Admiss. ambient temp.	0-40 °C
Dimensions	482 x 48 x 175 mm, 1 RS
Width	482 mm
Height	48 mm
Depth	175 mm
Rack units, RU	1
Weight	2.3 kg
Packaging dimensions (W x H x L)	0.18 x 0.047 x 0.482 m
Gross weight	3.035 kg
Net weight	2.32 kg
ULM-164/SW	
EAN code	4007754182781

ULM-164/SW

Net weight	2.32 kg