


WDE-130

Order no.: 1001434

PRODUCT INFORMATION

PA ceiling speaker

- 100 V transmission technology
- Very good transmission range
- Speaker (13 cm) with high sound pressure and very good transmission range
- Moisture-proof speaker cone
- Quick-mounting device
- Metal housing with metal protective grille
- 3 power taps via pressure clamps
- Ball-proof according to DIN 18 032, part 3

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

WDE-130

Transmission technology	100 V
Frequency range	70-19,000 Hz
Power rating (RMS)	6/3/1.5 W
SPL	93 dB/W/m
Max. rated SPL	103 dB
Radiation angle, horizontal	180°
Radiation angle, vertical	180°
Mounting cutout	Ø 140-150 mm
Dimensions	Ø 168 mm x 62 mm
Outside diameter	Ø 168 mm
Width	Ø 168 mm
Height	Ø 168 mm
Depth	62 mm
Colour	White, RAL 9010
Protective class	IP54
Weight	0.85 kg
Packing unit	1
Packaging dimensions (W x H x L)	0.187 x 0.187 x 0.075 m
Gross weight	1 kg
Net weight	0.9 kg

WDE-130

EAN code	4007754429688
Net weight	0.9 kg