

# WDR-245-CX30

Order no.: 1001497

## PRODUCT INFORMATION

**PA ceiling speaker**

- 100 V transmission technology
- 2-way speaker system (20 cm)
- High sound quality and balanced frequency response, distortion-free transmission of 60 Hz signals is also possible
- Quick-mounting device
- Metal housing with metal protective grille
- 3 power taps via pressure clamps
- Ball-proof in accordance with DIN 18 032, part 3

**Manufacturer information:**
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

# SPECIFICATIONS

**WDR-245-CX30**

| | |
|---|---|
| Transmission technology | 100 V |
| Frequency range | 60-20,000 Hz |
| Power rating (RMS) | 30/15/7.5 W |
| SPL | 95 dB/W/m |
| Max. rated SPL | 110 dB |
| Radiation angle, horizontal | 160° |
| Radiation angle, vertical | 160° |
| Mounting cutout | Ø 215-230 mm |
| Dimensions | Ø 252 mm x 120 mm |
| Outside diameter | Ø 252 mm |
| Width | Ø 252 mm |
| Height | Ø 252 mm |
| Depth | 120 mm |
| Colour | white, RAL 9010 |
| Weight | 2.5 kg |
| Packing unit | 1 |
| Type of speaker | 200 |
| Packaging dimensions (W x H x L) | 0.27 x 0.27 x 0.115 m |
| Gross weight | 2.6 kg |
| Net weight | 2.5 kg |

**WDR-245-CX30**

| | |
|---|---|
| EAN code | 4007754430301 |
| Net weight | 2.5 kg |